

LEDBELYSNING.NO

24V/48W LED Strømforsyning

Art.nr.: 600502

EGENSKAPER	PROPERTIES
Spesifikasjoner: Inngangsspenning: 200-240V AC~50Hz Utgangsspenning: 24V konstantspenning Maks. startstrøm: 75A ved 240V full last Inngangsstrøm: 0.8A maks. ved 240V Utgangsstrøm: 2000mA maks. Standbystrøm: 0.3W ved 240V ingen last Temperaturområde: -20°C til 40°C Relativ fuktighet: 20% til 90% Ripple og støy: 200mVp-p (maks.) Effektivitet: min. 80% ved 240V full last Forsinkelse før på: 3s maks. ved full last Forsinkelse før av: 10ms ved full last Switchefrekvens: 65KHz Forventet levetid: 50.000 timer ved 25°C Dimbar: Nei Sikkerhet: IP-grad: 20 Kortslutningsbeskyttelse: Ja (auto. omstart) Overspenningsbeskyttelse: Ja (auto. innhenting) Konstantspenningstype: SELV Standard(er)/direktiv: EN 61347-2-13: 2014+A1:2017; EN 61347-1:2015; EN 60598-1: 2015 + A1:2018; EN 62493: 2015; Low voltage directive 2014/35/EU Dimensjoner: Kabellengde: 1,2m Endekontakt: 5,5mm x 2,1mm DC jack	Specifications: Input voltage: 200-240V AC~50Hz Output voltage: 24V constant voltage Max. inrush current: 75A at 240V full load Input current: 0.8A max. at 240V Output current: 2000mA max. Standby current: 0.3W at 240V no load Temperature range: -20°C til 40°C Relative humidity: 20% til 90% Ripple and noise: 200mVp-p (max.) Efficiency: min. 80% at 240V full load On delay: 3s max. at full load Off delay: 10ms at full load Switching frequency: 65KHz Life expectancy: 50.000 hours at 25°C Dimmable: No Safety: Ingress protection: 20 Short-circuit protection: Yes (auto restart) High voltage protection: Yes (auto recovery) Constant voltage type: SELV Standard(s)/directive(s): EN 61347-2-13: 2014+A1:2017; EN 61347-1:2015; EN 60598-1: 2015 + A1:2018; EN 62493: 2015; Low voltage directive 2014/35/EU Measurements: Cable length: 1,2m End connector: 5,5mm x 2,1mm DC jack
INSTRUKSJONER	INSTRUCTIONS
24V/48W LED Strømforsyning til 24V konstantspennings LED-striper. Kan ikke dimmes. Plugges i stikkontakt. EU-plugg.	24V/48W LED Power Supply for 24V constant voltage LED-strips. Not dimmable. Plug directly in power outlet. EU-plug.

SKISSE

DRAWING

