

Datablad Blend | FROST

Art.nr.: 100304



EGENSKAPER	PROPERTIES
Elektrisk Forventet levetid: 50.000 timer Lampe (spenning): 36V DC Driver (spenning): 220-240V AC, 50Hz Strømtrekk LED: 135mA Strømtrekk driver: ≤0,05A Effekt LED: 5W Miljø og drift Driftstemperatur: -25 °C til 45 °C Oppbevaringstemperatur: -25 °C til 65 °C Relativ luftfuktighet: 8 % til 80 % Materialer: Aluminium, plast Lys Dimbar: Ja LED-type: COB (Chip on Board) Fargetemperatur: 2700K Fargegjengivelse (RA): ≥90 Lysstyrke: 380,7 lm ±5 % Effektivitet: 63,2 lm/W Blendingsgrad (UGR): <10 Lysspredning: 50° Sikkerhet Isolasjonsklasse (driver): II IP-grad: 20 IK-grad: 06 Kortslutningsbeskyttelse (driver): Ja Temperaturbeskyttelse (driver): Ja Overbelastningssikring (driver): Ja Dimensjoner Kassetmodul (B x H x D): 44,3 x 55 x 44,3 mm LED-spot utstikk (H): 7mm Totalhøyde (kassetmodul + LED-spot utstikk): 62,5 mm	Electrical Expected lifespan: 50,000 hours Lamp voltage: 36V DC Driver voltage: 220-240V AC, 50Hz LED current draw: 135mA Driver current draw: ≤0.05A LED power consumption: 5W Environmental and Operating Conditions Operating temperature: -25°C to 45°C Storage temperature: -25°C to 65°C Relative humidity: 8% to 80% Materials: Aluminum, plastic Light Dimmable: Yes LED type: COB (Chip on Board) Color temperature: 2700K Color rendering index (CRI): ≥90 Luminous flux: 380,7 lm ±5% Efficiency: 63,2 lm/W Glare rating (UGR): <10 Beam angle: 50° Safety Driver protection class: II IP rating: 20 IK rating: 06 Short-circuit protection (driver): Yes Thermal protection (driver): Yes Overload protection (driver): Yes Dimensions Cassette module (W x H x D): 44.3 x 55 x 44.3 mm LED protrusion (H): 7mm Total height (cassette module + LED protrusion): 62,5 mm

Monteringsanvisning for Blend Innfelt og Innsparklet Kasset: MONO, DI, TRI og TETRA

